

Reciprocating Air Compressor Oil

L-DAB 22, 32, 46, 68, 100, 150

Product Introduction

PetroChina Lubricant Company's L-DAB Reciprocating Air compressor Oil is blended with high quality base oils together with additives to cater to the use in air compressors. It has low tendency in deposits-forming, good thermal oxidation stability, etc. Its quality meets the international standard and requirement.

Applications

L-DAB compressor oil is suitable for all types of medium and high pressure reciprocating air compressors. It is also suitable for the lubrication and cooling of the variable volume compressors.

Special Properties

- Excellent thermal stability.
- Good anti-wear properties.
- Excellent demulsibility.
- Suppresses foaming.
- No corrosion to sealing materials or gaskets.

Bench Test and Mixing Test

- Bench test passed.
- Industrial field test passed.

Storage and Precaution

- All containers, tanks, pipelines and valves has to be cleaned thoroughly and inspected to be clean for use before being used to transfer or transport L-DAB 22, 32, 46, 68,100, 150 to prevent contamination.
- Storage tanks/equipment must be dedicated and is recommended to be stored in an indoor and controlled environment.
- Storage tanks/equipment must be waterproof, mist-proof and free from other mechanical particles.
- Product must be labeled clearly and properly during the entire transportation process to prevent mixing of other petrol-chemical product into the air compressor oil.